

Product Information



M-Balm™

Wood Epoxy for Consolidation of Rotted Wood for Interior and Exterior Use Solvent-Free * Reinforces * Waterproof

Penetrates deeply into deteriorated and rotted wood, creating a strong, solid base for restoration. After application, a patch may be built up with E-Wood, which can be finished in a normal manner. Use for repair of rotted and deteriorated, dried out or spongy wood. Excellent for both interior and exterior use. M-Balm penetrates deep into the wood, hardening into a strong, water resistant mass.

Directions:



Mix two parts of M-Balm Epoxy (Part A) with one part of M-Balm Hardener (Part B) by volume. Mix no more that can be applied within 30 minutes. For easy measurement, use mixing/applicator squeeze bottle.

Application:

Apply to affected area with mixing/applicator squeeze bottle, syringe, brush or roller. The wood must be very dry (15% moisture content or less). Repeat if necessary.

Technique:

In extreme cases of deep rot, drill a series of holes into the decayed area and pour liberally into the affected area. Allow time for M-Balm to soak well into the area. Repeat if necessary.

Cleanup:

Uncured mixed M-Balm (Part A and Part B) may be cleaned up with white vinegar then flushed with water.

Coverage:

Depends on porosity of wood.

Packaging:

M-Balm is available in 24-oz. bottles and 1.5-gallon containers.

Drying Time:

12 to 24 hours. M-Balm cures slower in low temperatures. (Never change mixing rates to compensate for temperature.)

Shelf Life/Application Temperature:

M-Balm has a shelf life of 1 year. Application temperature is between 40° to 90°. Do not freeze!

Safety:

Always wear protective disposable gloves when using this product. Avoid skin contact. Skin sensitization may result from prolonged and repeated contact. If use causes soreness, redness, blistering, or other symptoms of irritation, stop use and see a physician immediately. Use with adequate ventilation. If eye contact occurs, flush with large quantities of water and contact a physician immediately. Do not use around open flame. If **Part A** is swallowed, induce vomiting. If **Part B** is swallowed, **Do Not** induce vomiting. **Keep out of reach of children.**

The Log Home Care and
Maintenance Authority

Company Stores

Washington/Western
Division

1-800-548-1231

Tennessee/Eastern
Division

1-800-548-3554

Sevierville, TN

1-888-441-1116

Minnesota Branch

1-877-244-6548

Colorado Branch

1-800-433-8781

Montana Branch

1-800-479-7090

Stocking Distributors

Canadian Log Home
Supply, Ontario

1-800-746-7773

Hess Log Home Supply,
PA

1-800-257-4864

Log Home Center &
Supply, IN

1-800-773-6223

Steels Industrial
Products, Ltd., B.C.

(250) 374-3151

Timeless Wood Care
Products, MI

1-800-564-2987

visit us
online
www.permachink.com